

DECK HARDWARE

60mm Block



B300601B



B300602B



B300603B



B300604B



B300605B



B300621B



B300622B



B300623B



B300624B



B300671B



B300672B



B300681B



B300682B



B300683B



B300684B



Core benefits

- High-tech composite material
- Spherical plain bearings
- Large range
- Extensive range of fastening alternatives
- Adjustable clam cleats
- For rope diameters of 6-14mm

Black line 60mm

Part no	Product description	A		B		C		Rope diameter [mm]	Weight [gr]
		Sheave Ø [mm]	Length [mm]	Shackle pin Ø [mm]	Safe working load [kg]	Breaking load [kg]			
B300601B	Single	60	94	6	1150	2100	6 - 14	205	
B300602B	Single w becket	60	118	6	1150	2100	6 - 14	220	
B300603B	Single w cam	60	94	6	1150	2100	6 - 14	305	
B300604B	Single w cam & becket	60	118	6	1150	2100	6 - 14	320	
B300605B	Single w strap head	60	94	-	1150	2100	6 - 14	140	
B300621B	Fiddle	60/35	142	6	1150	2100	6 - 14	265	
B300622B	Fiddle w becket	60/35	164	6	1150	2100	6 - 14	279	
B300623B	Fiddle w cam	60/35	142	6	1150	2100	6 - 14	370	
B300624B	Fiddle w cam & becket	60/35	164	6	1150	2100	6 - 14	375	
B300671B	Double	60	94	8	1150	2100	6 - 14	350	
B300672B	Double w becket	60	118	8	1150	2100	6 - 14	360	
B300681B	Triple	60	94	6	1150	2100	6 - 14	390	
B300682B	Triple w becket	60	118	6	1150	2100	6 - 14	404	
B300683B	Triple w cam	60	94	6	1150	2100	6 - 14	490	
B300684B	Triple w cam & becket	60	118	6	1150	2100	6 - 14	500	

Maximum load of cams is 200 kg



B700601

Core benefits

- Best quality stainless steel
- Numerous sizes
- Elegant design
- For wire diameters of 6-7mm

Wire Block

Part no	Product description	A	B	C	Safe working load [kg]	Breaking load [kg]	Wire diameter [mm]	Weight [gr]
		Sheave Ø [mm]	Length [mm]	Pin Ø [mm]				
B700601	Wire block	60	93	8	1500	3000	6 - 7	175



B300644B



B300645B



B300646B

Cheek blocks

Part no	Product description	A	D	E	Safe working load [kg]	Breaking load [kg]	Rope diameter [mm]	Weight [gr]
		Sheave Ø [mm]	Length [mm]	Width [mm]				
B300644B	Cheek block flat plate	60	98	57	800	1600	6 - 14	240
B300645B	Cheek block horizontal plate ¹	60	110	50/21	800	1600	6 - 14	240
B300646B	Cheek block curved plate ²	60	97	55	800	1600	6 - 14	240

M5 mounting screws

¹ Recommended profile radius 190 - 400mm

² Recommended profile radius 30 - 50mm

