

SWIVELS



STANDARD/STANDARD

LARGE/LARGE

LARGE/CLEVIS

CLEVIS/CLEVIS

STANDARD/CLEVIS

STANDARD/LARGE

Swivel types com in each size T5, T8, T12, T20, T30, T40, T50 and any combination of bails including standard/standard, standard/large, standard/clevis, large/large, large/clevis, and clevis/clevis. Contact Tylaska for specific configuration and pricing.

Loose Bails

Individual bails available for use as standoffs, termination fittings or in special rigging applications. All sizes and configurations available for special rigging applications



INDIVIDUAL LINKED BAILS

SWIVEL TYPE	A in (mm)	B in (mm)	WORK LOAD lb (kg)	BREAKING STRENGTH lb (kg)
T5 SB	.398 (10.1)	.625(15.9)	2,500 (1,136)	5,000 (2,273)
T5 LB	.398 (10.1)	.712 (18.1)	2,500 (1,136)	5,000 (2,273)
T5 CB	.398 (10.1)	.625(15.9)	2,500 (1,136)	5,000 (2,273)
T8 SB	.398 (10.1)	.685 (17.4)	4,000 (1,818)	8,000 (3,636)
T8 LB	.398 (10.1)	.838 (21.3)	4,000 (1,818)	8,000 (3,636)
T8 CB	.398 (10.1)	.685(17.4)	4,000 (1,818)	8,000 (3,636)
T12 SB	.476 (12.1)	.889 (22.6)	6,000 (2,727)	12,000 (5,455)
T12 LB	.476 (12.1)	.974 (24.7)	6,000 (2,727)	12,000 (5,455)
T12 CB	.476 (12.1)	.889 (22.6)	6,000 (2,727)	12,000 (5,455)
T20 SB	.638 (16.2)	1.074 (27.3)	10,000 (4,545)	20,000 (9,091)
T20 LB	.638 (16.2)	1.215 (30.9)	10,000 (4,545)	20,000 (9,091)
T20 CB	.638 (16.2)	1.074 (27.3)	10,000 (4,545)	20,000 (9,091)
T30 SB	.795 (20.2)	1.460 (37.1)	15,000 (6,818)	30,000 (13,630)
T30 LB	.795 (20.2)	1.560 (39.6)	15,000 (6,818)	30,000 (13,630)
T30 CB	.795 (20.2)	1.460 (37.1)	15,000 (6,818)	30,000 (13,630)
T40 SB	.960 (24.4)	1.671 (42.4)	20,000 (9,091)	40,000 (18,182)
T40 LB	.960 (24.4)	2.083 (52.9)	20,000 (9,091)	40,000 (18,182)
T40 CB	.960 (24.4)	1.671 (42.4)	20,000 (9,091)	40,000 (18,182)
T50 SB	1.200 (30.5)	2.433 (61.8)	25,000 (11,364)	50,000 (22,727)
T50 LB	1.200 (30.5)	3.472 (88.2)	25,000 (11,364)	50,000 (22,727)
T50 CB	1.200 (30.5)	2.433 (61.8)	25,000 (11,364)	50,000 (22,727)



SB - Standard Bails
LB - Large Bails
CB - Clevis Bails